## ecodesign<sub>2022</sub>

## DECLARATION ACCORDING COMMISSION REGULATION (EU) 2015/1185 April 2015 and ACCORDING COMMISSION DELEGATED REGULATION (EU) 2015/1186 April 2015

| Information requirements for solid fuel local space heaters |   |  |  |  |  |  |
|---|---|--|--|--|--|--|
| Model/Name:   | A11 V ROUND TOP COAX / A11 C ROUND TOP COA> |  |  |  |  |  |
| Trademark:  | NOBIS                                       |  |  |  |  |  |
| Indirect heating functionality:                             | No  |  |  |  |  |  |
| Direct heat output:   | 10,2  |  |  |  |  |  |
| Indirect heat output:                                       |   |  |  |  |  |  |
|   |   |  |  |  |  |  |

| Fuel:   | Preferred<br>fuel: | Other<br>suitable<br>fuel(s): | ŋ₅% (*) | nom<br>P | e heatin<br>iinal heo<br>COG<br>ng/Nm <sup>3</sup> | at outp<br>CO | ut (*)<br>NOX | minin<br>P | heating<br>num he<br>COG<br>ng/Nm <sup>3</sup> | at outp<br>CO | out (*)<br>NOX |
|---|--------------------|-------------------------------|---------|----------|--|---------------|---------------|------------|--|---------------|----------------|
| Wood logs with moisture content $\leq$ 25 %   | No                 | No                            |         |          |  |               |               |            |  |               |                |
| Compressed wood with moinsture content < 12 % | Yes                | No                            | 88,5    | 9,9      | 1  | 64            | 65            | 16,3       | 3  | 98            | 68             |

| Characteristics when operating with the preferred fuel only |                  |      |    |  |  |  |
|---|------------------|------|----|--|--|--|
| Heat output   |                  |      |    |  |  |  |
| Nominal heat output:  | P <sub>nom</sub> | 10,2 | kW |  |  |  |
| Minimum heat output (indicative):                           | P <sub>min</sub> | 4,56 | kW |  |  |  |

| Useful efficiency (NCV as received)                    |                     |      |   |  |  |  |
|--|---------------------|------|---|--|--|--|
| Useful efficiency at nominal heat output:              | η <sub>th,nom</sub> | 92,5 | % |  |  |  |
| Useful efficiency at minimum heat output (indicative): | $\eta_{th,min}$     | 92,7 | % |  |  |  |

| Auxiliary electricity consumption |                   |       |    |  |  |
|-----------------------------------|-------------------|-------|----|--|--|
| At nominal heat output:           | el <sub>max</sub> | 0,079 | kW |  |  |
| At minimum heat output:           | el <sub>min</sub> | 0,078 | kW |  |  |
| In standby mode:                  | el <sub>SB</sub>  | 0,002 | kW |  |  |

| Permanent pilot flame power requirement                    |                    |  |     |  |  |  |
|--|--------------------|--|-----|--|--|--|
| Pilot flame power requirement:                             | P <sub>pilot</sub> |  | kW  |  |  |  |
|  | [                  |  | No  |  |  |  |
| Type of heat output/room temperature control F(2):         | Single stage h     | Single stage heat output, no room temperature control  |     |  |  |  |
|  | Two or more r      | Two or more manual stages, no room temperature control |     |  |  |  |
|  | With mechan        | With mechanic thermostat room temperature control      |     |  |  |  |
|  | With electron      | No   |     |  |  |  |
|  | With electron      | No   |     |  |  |  |
|  | With electron      | c room temperature control plus week timer             | Yes |  |  |  |
|  | Room tempe         | No   |     |  |  |  |
| Other control options F(3) (multiple selections possible): | Room tempe         | No   |     |  |  |  |
|  | With distance      | control option   | Yes |  |  |  |
| Energy efficiency class:                                   |                    | A++  |     |  |  |  |
| Energy efficiency index (EEI):                             |                    | 130  |     |  |  |  |

Note:

(\*)ns = seasonal energy efficiency, PM = particolate matter, OGC = organic gaseous compounds, CO = carbon monoxide, Nox = nitrogen oxides



www.nobisfire.it