

DECLARATION ACCORDING COMMISSION REGULATION (EU) 2015/1185 April 2015 and ACCORDING COMMISSION DELEGATED REGULATION (EU) 2015/1186 April 2015

Inform	ation requiren	nents for solid f	uel local spac	ce heat	ers							
Model/Name:					HB14 V ULISSE /							
Trademark:					NOBIS							
Indirect heating functionality:					Yes							
Direct heat output:					3,2							
Indirect heat output:					14,6							
Fuel:	Preferred fuel:	Other suitable fuel(s):	n _s % (*)	Spece heating emissions at nominal heat output (*)					e heating emissions at mum heat output (*)			
				P		CO (13% C		P n	COG ng/Nm³	CO (13% C		
Wood logs with moisture content ≤ 25 %	No	No										
Compressed wood with moinsture content < 12 %	Yes	No	92	7,2	2	16	79	3,3	2	28	85	
		1		-				I				
Characteristics when operating with the preferred fuel only												
Heat output												
Nominal heat output:	P _{nom}		17,8					kW				
Minimum heat output (indicative):	P _{min}		8,4					kW				
	Useful eff	ficiency (NCV a	is received)									
Useful efficiency at nominal heat output:	η _{th,nom}	<u> </u>	94,2					%				
Useful efficiency at minimum heat output (indicative)	η _{th,min}		94,8					%				
	Auxiliar	y electricity co	nsumption									
At nominal heat output:	el _{max}	<u> </u>	0,016 kW									
At minimum heat output:	el _{min}		0,011						kW			
In standby mode:	el _{SB}		0,001 k						kW			
	Permanent r	pilot flame pow	er requireme	nt								
Pilot flame power requirement:	P _{pilot}							kW				
nist name perior regularies.		· piloi								K		
	Single stage heat output, no room temperature control No											
	Two or more manual stages, no room temperature control								No			
Type of heat output/room temperature control F(2):	With mechanic thermostat room temperature control							No				
	With electronic room temperature control							No				
	With electronic room temperature control plus day timer							No				
	With electronic room temperature control plus week timer Yes											
	Room temperature control, with presence detection							No				
Other control options F(3) (multiple selections possible	Room temperature control, with open window detection							No				
	With distance control option							Yes				
Energy efficiency class:						.++						
Energy efficiency index (EEI):												
Livingy Giliciency index (LLI).						J4						

.

Note:

 $(*)\eta_s$ = seasonal energy efficiency, PM = particolate matter, OGC = organic gaseous compounds, CO = carbon monoxide, Nox = nitrogen oxides

